



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS
 2. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 4. TEFLON

11	NUT	NOTE 1	NOTE 2	1	NUT-51632-24
10	FERRULE	COPPER	NOTE 2	1	FR-533-648-127C
9	WASHER	NOTE 1	NOTE 2	1	WS-90-128-08
8	SPRING	SK5	NOTE 2	1	900-1000-6
7	RETAINER RING	NOTE 1	NOTE 2	1	900-1000-5
6	GASKET	RUBBER	RED	1	GS-80-115-15
5	CONTACT PIN	NOTE 1	NOTE 3	1	71628-1112A2-5-1.2
4	INSULATOR	NOTE 4	NATURAL	1	71628-1112A2-4-50T
3	BARREL	NOTE 1	NOTE 2	1	71628-1112A2-3-06
2	HOUSING	NOTE 1	NOTE 2	1	71628-1112A2-2
1	SHELL	NOTE 1	NOTE 2	1	900-1000-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			PART NO.		
UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED		
0.5-6	=	±0.2	DATE	10-04-'12	
6-30	=	±0.4	CHECKED	DATE	
30-120	=	±0.6		10-04-'12	
120-315	=	±1	DRAWN	DATE	
315-1000	=	±1.6		10-04-'12	
1000-2000	=	±2.4			
SCALE	3/1	ISSUE	A		

G.L.I.	
TITLE	BNC R/A CRIMP PLUG (FOR RG-58, 58A, 58C, 141, LMR195)
DRAWING NO.	900-1112A2-06-50
FILE NO.	R:\D\G\DWG\900\1112A2\06\50

1. CRIMPED FERRULE
 HEX CRIMP SIZE .213"
 2. CONTACT PIN TO SOLDER